

HSS Nova 25 core bit with 3/4 in Weldon holder

Order number:: 6 31 34 300 05 1

Industrial standard. Metric dimensions, cutting depth 25 mm.

Bore Ø 30 mm



Suitable for:

KBE 30 (KBE 30), KBE 35 (KBE 35), KBE 50-2 (KBE 50-2), KBE 50-2 M (KBE 50-2 M), KBE 65-2 M (KBE 65-2 M), KBC 35 (KBC 35), KBB 40 (KBB 40), AKBU 35 PMQ (AKBU 35 PMQ), AKBU 35 PMQW (AKBU 35 PMQW), AKBU 35 PMQ Select (AKBU 35 PMQ), AKBU 35 PMQW Select (AKBU 35 PMQW), KBU 35 Q (KBU 35 Q), KBU 35 QW (KBU 35 QW), KBU 35-2 Q (KBU 35-2 Q), KBU 35-2 QW (KBU 35-2 QW), KBU 35 MQ (KBU 35 MQ), KBU 35 MQW (KBU 35 MQW), KBM 50 Q (KBM 50 Q), KBM 50 U (KBM 50 U), KBM 65 U (KBM 65 U), KBM 80 U (KBM 80 U), KBM 50 auto (KBM 50 auto), KBM 80 auto (KBM 80 auto)