



# HSS Dura 2 in core bit with Weldon holder

Order number:: 6 31 34 159 07 6

TiN surface coating for outstanding service lives and the best glide properties.

Imperial dimensions, cutting depth 2 in/50 mm.

Bore Ø 5/8 in

Bore Ø 15,88 mm

FEIN. Unverwüstliche  
Elektrowerkzeuge.



## Suitable for:

KBE 30 (KBE 30), KBE 65-2 M (KBE 65-2 M), KBB 40 (KBB 40), AKBU 35 PMQ (AKBU 35 PMQ), AKBU 35 PMQW (AKBU 35 PMQW), AKBU 35 PMQ Select (AKBU 35 PMQ), AKBU 35 PMQW Select (AKBU 35 PMQW), KBU 35 Q (KBU 35 Q), KBU 35 QW (KBU 35 QW), KBU 35-2 Q (KBU 35-2 Q), KBU 35-2 QW (KBU 35-2 QW), KBU 35 MQ (KBU 35 MQ), KBU 35 MQW (KBU 35 MQW), KBM 50 Q (KBM 50 Q), KBM 50 U (KBM 50 U), KBM 65 U (KBM 65 U), KBM 50 auto (KBM 50 auto), KBM 80 auto (KBM 80 auto)