



Hardmetalen zaagblad

Voor het uitsnijden van beschadigde tegelvoegen. Ook voor het frezen van sleuven in pleisterwerk, gasbeton en soortgelijke bouwmaterialen evenals voor het reinigen en nabewerken van strokendemvoegen. Niet geschikt voor zeer harde epoxyhars- of cementvoegen. Het rendabele alternatief voor diamantgereedschappen.

Extra dunne uitvoering. Zaagbreedte ca. 1,2 mm. Gesegmenteerd, ideaal voor het werken in hoeken en langs randen zonder oversnijden.

41,50 € excl. BTW

Productnummer: 6 35 02 170 21 0

Technische gegevens

ALGEMENE TECHNISCHE GEGEVENS

Ø

90 mm

Houder

SLP

VE (verpakkings eenheid)

1 St

Geschikt voor de volgende machines

- > Accu MULTIMASTER AMM 500 Plus Top 4 Ah AS
- > Accu MULTIMASTER AMM 500 Plus Top AS
- > Accu MULTIMASTER AMM 500 Plus AS
- > Accu MULTIMASTER AMM 700 Max Top 4 Ah AS
- > Accu MULTIMASTER AS
- > Accu MULTIMASTER AMM 700 Max AS
- > Accu MULTIMASTER AMM 700 Max Top AS
- > MULTIMASTER MM 300 Plus Start
- > Accu Multimaster AMM 500 AS 2 Ah in nylon tas
- > Accu Multimaster AMM 500 PLUS 4 Ah in nylon tas
- > Accu MULTIMASTER AMM 700 Max AS 4 Ah in nylon tas

Toepassingsvoorbeelden

