



Broca anelar HSS Dura 50 com mandril QuickIN

Revestimento da superfície em TiN para ótima durabilidade e excelentes características de desliz. Dimensões em metros, profundidade de corte de 50 mm.

97,85 € P.V.P sem IVA

N.º pedido: 6 31 33 320 06 8

Dados técnicos

DADOS GERAIS

Profundidade de corte

50 mm

Ø orifício

32 mm

Adaptável para as seguintes máquinas

Universal

- > KBM 65 U
- > KBM 50 Q
- > KBM 50 UQW
- > KBM 65 UQW
- > KBM 50 U
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > KBU 35 PQ
- > KBU 35 PQW
- > KBU 35-2 QW
- > KBU 35 MQW
- > KBU 35 QW
- > KBU 35-2 Q
- > KBU 35 MQ
- > KBU 35 Q
- > Conjunto Construction-Site AKBU 35 PMQW 18 V AS 2x 8 Ah Weldon 3/4 in / HSS NOVA 50
- > Conjunto Construction-Site AKBU 35 PMQW 18 V
- > AS 1x 12 Ah Weldon 3/4 in / HSS NOVA 50
- > Conjunto Construction-Site AKBU 35 PMQW AS Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > Conjunto AKBU 35 PMQW 18 V AS 2x 8 Ah
- > AKBU 35 PMQW AS
- > AKBU 35 PMQ AS



Automatic

> KBM 50 auto QW

> KBM 50 auto