



FEIN



Broca anelar HSS Dura 50 in com mandril 3/4 in Weldon

Revestimento da superfície em TiN para ótima durabilidade e excelentes características de deslize.

Dimensões em metros, profundidade de corte de 50 mm.

45,70 € P.V.P sem IVA

N.º pedido: 6 31 34 120 07 6

Dados técnicos

DADOS GERAIS

Profundidade de corte

50 mm

Ø orifício

12 mm

Adaptável para as seguintes máquinas

Universal

- > KBU 35 Q
- > KBU 35 MQ
- > KBU 35-2 Q
- > KBU 35 QW
- > KBU 35 MQW
- > KBU 35-2 QW
- > KBU 35 PQW
- > KBU 35 PQ
- > KBM 50 U
- > KBM 50 Q
- > KBM 65 U
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBM 50 UQW
- > KBM 65 UQW
- > AKBU 35 PMQ AS
- > AKBU 35 PMQW AS
- > Conjunto AKBU 35 PMQW 18 V AS 2x 8 Ah
- > AKBU 35 PMQW 18 V AS
- Set 1x 12 Ah
- > Conjunto Construction-Site AKBU 35 PMQW AS Weldon 3/4 in / HSS NOVA 50
- > Conjunto Construction-Site AKBU 35 PMQW 18 V AS 1x 12 Ah Weldon 3/4 in / HSS NOVA 50
- > Conjunto Construction-Site AKBU 35 PMQW 18 V AS 2x 8 Ah Weldon 3/4 in / HSS NOVA 50

Endurance

- > KBE 50-2
- > KBE 32
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > Conjunto Fabrication KBE 36 QW MAGSPEED

Automatic

- > KBM 50 auto
- > KBM 50 auto QW