



FEIN



Carota HSS Nova 25 cu prindere QuickIN

Standard industrial. Dimensiuni metrice, adâncime găurire 25 mm.

Numărul produsului: 6 31 33 250 05 1

Specificații

SPECIFICAȚII GENERALE

Adâncime de găurire

25 mm

Ø de găurire

25 mm

Suitable for the following machines

Universal

- > KBM 50 UQW
- > AKBU 35 PMQ AS
- > KBM 65 UQW
- > KBM 65 U
- > AKBU 35 PMQW 18V AS Construction-Site 1x 12Ah set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW 18V AS Construction-Site 2x 8Ah set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW AS Construction-Site, set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > AKBU 35 PMQW 18V AS set 2x 8Ah
- > AKBU 35 PMQW AS
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > KBU 35 Q
- > KBM 50 Q
- > KBM 50 U
- > KBU 35 PQ
- > KBU 35 PQW
- > KBU 35-2 QW
- > KBU 35 MQW
- > KBU 35 QW
- > KBU 35-2 Q
- > KBU 35 MQ

Automatic



FEIN

> KBM 50 auto QW

> KBM 50 auto