



Carota HSS Dura 25, cu prindere QuickIN

Suprafața de tăiere cu acoperire TiN, pentru durată de viață lungă și proprietăți optime de alunecare.

Dimensiuni metrice, adâncime găurire 25 mm.

Numărul produsului: 6 31 33 180 06 7

Specificații

SPECIFICAȚII GENERALE

Adâncime de găurire

25 mm

Ø de găurire

18 mm

Suitable for the following machines

Universal

- > KBM 65 U
- > KBM 65 UQW
- > AKBU 35 PMQ AS
- > KBM 50 Q
- > KBM 50 UQW
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > KBM 50 U
- > KBU 35 PQ
- > KBU 35 PQW
- > KBU 35-2 QW
- > KBU 35 MQW
- > KBU 35 QW
- > KBU 35-2 Q
- > KBU 35 MQ
- > KBU 35 Q
- > AKBU 35 PMQW 18V AS Construction-Site 2x 8Ah set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW 18V AS Construction-Site 1x 12Ah set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW AS Construction-Site, set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > AKBU 35 PMQW 18V AS set 2x 8Ah
- > AKBU 35 PMQW AS



Automatic

> KBM 50 auto QW

> KBM 50 auto