



Carota HSS Dura 25, cu prindere 3/4" Weldon

Suprafața de tăiere cu acoperire TiN, pentru durată de viață lungă și proprietăți optime de alunecare.

Dimensiuni metrice, adâncime găurire 25 mm.

Numărul produsului: 6 31 34 220 07 5

Specificații

SPECIFICAȚII GENERALE

Adâncime de găurire

25 mm

Ø de găurire

22 mm

Suitable for the following machines

Universal

- | | | |
|---|---|--|
| > AKBU 35 PMQ AS | Weldon 3/4 in / HSS | > KBU 35 PQW |
| > AKBU 35 PMQW AS | NOVA 50 | > KBU 35 PQ |
| > AKBU 35 PMQW 18V AS
set 2x 8Ah | > AKBU 35 PMQW 18V AS
Construction-Site 2x 8Ah
set cu prindere Weldon
3/4 in / HSS NOVA 50 | > KBM 50 U |
| > AKBU 35 PMQW 18 V AS
Set 1x 12 Ah | > KBU 35 Q | > KBM 50 Q |
| > AKBU 35 PMQW AS
Construction-Site, set cu
prindere Weldon 3/4 in /
HSS NOVA 50 | > KBU 35 MQ | > KBM 65 U |
| > AKBU 35 PMQW 18V AS
Construction-Site 1x
12Ah set cu prindere | > KBU 35-2 Q | > KBU 35 QW Structural
Steel-Set 3/4 in Weldon |
| | > KBU 35 QW | > KBU 35 QW Fabricator
M12 Tapping-Set 3/4 in
Weldon |
| | > KBU 35 MQW | > KBM 50 UQW |
| | > KBU 35-2 QW | > KBM 65 UQW |



Endurance

- > KBE 50-2
- > KBE 32
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > KBE 36 QW MAGSPEED Fabrication Set

Automatic

- > KBM 50 auto
- > KBM 50 auto QW