



Carota HSS Dura 25, cu prindere 3/4" Weldon

Suprafața de tăiere cu acoperire TiN, pentru durată de viață lungă și proprietăți optime de alunecare.

Dimensiuni metrice, adâncime găurire 25 mm.

Numărul produsului: 6 31 34 250 07 5

Specificații

SPECIFICAȚII GENERALE

Adâncime de găurire

25 mm

Ø de găurire

25 mm

Suitable for the following machines

Universal

- > KBU 35 Q
- > KBU 35 MQ
- > KBU 35-2 Q
- > KBU 35 QW
- > KBU 35 MQW
- > KBU 35-2 QW
- > KBU 35 PQW
- > KBU 35 PQ
- > KBM 50 U
- > KBM 50 Q
- > KBM 65 U
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBM 50 UQW
- > KBM 65 UQW
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > AKBU 35 PMQ AS
- > AKBU 35 PMQW AS
- > AKBU 35 PMQW 18V AS set 2x 8Ah
- > AKBU 35 PMQW 18 V AS
- Set 1x 12 Ah
- > AKBU 35 PMQW AS Construction-Site, set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW 18V AS Construction-Site 1x 12Ah set cu prindere Weldon 3/4 in / HSS NOVA 50
- > AKBU 35 PMQW 18V AS Construction-Site 2x 8Ah set cu prindere Weldon 3/4 in / HSS NOVA 50



Endurance

- > KBE 50-2
- > KBE 32
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > KBE 36 QW MAGSPEED Fabrication Set

Automatic

- > KBM 50 auto
- > KBM 50 auto QW