



HSS Dura 50-kärnborr med 3/4 in Weldonfäste

TiN-ytbeläggningen ger suverän livslängd och bättre glideegenskaper.

Sl-mått, borrhjup 50 mm.

Best.nr: 6 31 34 150 07 6

Tekniska specifikationer

ALLMÄN TEKNISK INFORMATION

Skärdjup

50 mm

Borr-Ø

15 mm

Lämplig för följande maskiner

Universal

- > KBU 35 Q
- > KBU 35 MQ
- > KBU 35-2 Q
- > KBU 35 QW
- > KBU 35 MQW
- > KBU 35-2 QW
- > KBU 35 PQW
- > KBU 35 PQ
- > KBM 50 U
- > KBM 50 Q
- > KBM 65 U
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBM 50 UQW
- > KBM 65 UQW
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > AKBU 35 PMQ AS
- > AKBU 35 PMQW AS
- > AKBU 35 PMQW 18 V AS sats 2 st. 8 Ah
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > AKBU 35 PMQW AS Construction-Site-sats 3/4 tum Weldon/HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Construction-Site 1 st. 12 Ah sats 3/4 in Weldon/HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Construction-Site 2 st. 8 Ah sats 3/4 tum Weldon/HSS NOVA 50



Endurance

- > KBE 50-2
- > KBE 32
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > KBE 36 QW MAGSPEED
Fabrication-Sats

Automatic

- > KBM 50 auto
- > KBM 50 auto QW