



HSS Dura 25-kärnborr med 3/4 in Weldonfäste

TiN-ytbeläggningen ger suverän livslängd och bättre glideegenskaper.

Sl-mått, borrhjup 25 mm.

Best.nr: 6 31 34 320 07 5

Tekniska specifikationer

ALLMÄN TEKNISK INFORMATION

Skärdjup

25 mm

Borr-Ø

32 mm

Lämplig för följande maskiner

Universal

- > AKBU 35 PMQ AS
- > AKBU 35 PMQW AS
- > AKBU 35 PMQW 18 V AS
sats 2 st. 8 Ah
- > AKBU 35 PMQW 18 V AS
Set 1x 12 Ah
- > AKBU 35 PMQW AS
Construction-Site-sats
3/4 tum Weldon/HSS
NOVA 50
- > AKBU 35 PMQW 18 V AS
Construction-Site 1 st. 12
- Ah sats 3/4 in
Weldon/HSS NOVA 50
- > AKBU 35 PMQW 18 V AS
Construction-Site 2 st. 8
Ah sats 3/4 tum
Weldon/HSS NOVA 50
- > KBU 35 Q
- > KBU 35 MQ
- > KBU 35-2 Q
- > KBU 35 QW
- > KBU 35 MQW
- > KBU 35-2 QW
- > KBU 35 PQW
- > KBU 35 PQ
- > KBM 50 U
- > KBM 50 Q
- > KBM 65 U
- > KBU 35 QW Structural
Steel-Set 3/4 in Weldon
- > KBU 35 QW Fabricator
M12 Tapping-Set 3/4 in
Weldon
- > KBM 50 UQW
- > KBM 65 UQW



Automatic

- > KBM 50 auto
- > KBM 50 auto QW

Endurance

- > KBE 50-2